

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GRF UNI-100 BO 250ML*24 ENDE
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International B.V.

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)

GB

www.griffon.eu 1/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms









GHS02 GHS05 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

cyclohexanone

tetrahydrofuran

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

- Labelling of packages where the contents do not exceed 125 ml
- · Hazard pictograms









GHS02 GHS05 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

cyclohexanone tetrahydrofuran

Hazard statements

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 3)

- GF

www.griffon.eu 2/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

(Contd. of page 2)

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

Determination of endocrine-disrupting properties

78-93-3 Butanone

List II

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description**: Adhesive

· Dangerous components:		
CAS: 109-99-9 EINECS: 203-726-8 Index number: 603-025-00-0 Reg.nr.: 01-2119444314-46	tetrahydrofuran	≥50-<80%
CAS: 108-94-1 EINECS: 203-631-1 Index number: 606-010-00-7 Reg.nr.: 01-2119453616-35	cyclohexanone	10-25%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43- XXXX	Butanone ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥2.5-<10%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119565113-46 01-2119555270-46	Butylated hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Call a doctor immediately.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)

- GB

www.griffon.eu 3/13



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

(Contd. of page 3)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- After swallowing: Rinse out mouth and then drink plenty of water.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

(Contd. on page 5)

GB

www.griffon.eu 4/13



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

(Contd. of page 4)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with	limit values that	t require monit	oring at the	workplace:
------------------	-------------------	-----------------	--------------	------------

109-99-9 tetrahydrofuran

WEL Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm

108-94-1 cyclohexanone

WEL Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm Sk, BMGV

78-93-3 Butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

· DNELs

78-93-3 Butanone

Oral Consumer, oral, longterm exposition

Dermal Worker, dermal, longterm exposition
Consumer, dermal, longterm exposition
Inhalative Worker, inhalative, longterm exposition
Consumer, inhalative, longterm exposition
Consumer, inhalative, longterm exposition
Consumer, inhalative, longterm exposition
Consumer inhalative, longterm exposition
Consumer inhalative, longterm exposition
Consumer inhalative, longterm exposition
Consumer inhalative inhalati

· PNECs

78-93-3 Butanone

Oral Secondary Poisoning 1000 mg/kg
Fresh water 55.8 mg/l
Fresh water sediment 284.7 mg/kg

Fresh water sediment 284.7 mg/kg dry weight

Marine water 55.8 mg/l

Marine sediment 284.7 mg/kg dry weight

Soil 22.5 mg/kg

(Contd. on page 6)

GB

www.griffon.eu 5/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

Sewage treatment plant	709 mg/l
Sporadic release	55.8 mg/l

· Ingredients with biological limit values:

108-94-1 cyclohexanone

BMGV 2 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: cyclohexanol

78-93-3 Butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

Suitable respiratory protective device recommended.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

- · Recommended filter device for short term use: Filter A
- · Hand protection

Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

(Contd. on page 7)

GB

www.griffon.eu 6/13



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

(Contd. of page 6)

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

Body protection:

Use protective suit.

Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification • Odour: According to product specification Characteristic

· Odour threshold: Not determined.

• Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range 65.5 °C

• Flammability Highly flammable.

· Lower and upper explosion limit

Lower: 1.3 Vol %
 Upper: 12 Vol %
 Flash point: -21 °C

Auto-ignition temperature: 230 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 1450 mPas

Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined. Vapour pressure at 20 °C: 200 hPa

· Vapour pressure at 20 °C: 200 hPa · Vapour pressure at 50 °C: 550 hPa

Density and/or relative density

Density at 20 °C: 1.023 g/cm³ Relative density Not determined.

(Contd. on page 8)

- GB

www.griffon.eu 7/13



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

	(Contd. of page
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of hea	alth
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
	explosive air/vapour mixtures are possible.
Solvent content:	·
Organic solvents:	78.8 %
Water:	0.0 %
VOC (EC)	78.77 %
Solids content:	21.0 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haza	ard
classes	ai u
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Corrosive action on metals.
- 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 9)

- GE

www.griffon.eu 8/13



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

(Contd. of page 8)

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:				
109-99-9 1	109-99-9 tetrahydrofuran			
Oral	LD50	2500 mg/kg (rat)		
108-94-1	cyclohexa	none		
Oral	LD50	1800 mg/kg (rat)		
Dermal	LD50	1100 mg/kg (rabbit)		
Inhalative	LC50/4 h	11 mg/l (rat)		
78-93-3 B	78-93-3 Butanone			
Oral	LD50	>2193 mg/kg (rat)		
Dermal	LD50	>8050 mg/kg (rat)		
128-37-0 I	128-37-0 Butylated hydroxytoluene			
Oral	LD50	890 mg/kg (rat)		

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Suspected of causing cancer.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards

Endocrine	aisrupting	properties

78-93-3 Butanone List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 10)

- 00

www.griffon.eu 9/13



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

(Contd. of page 9)

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTIO	N 14·	Transport	information	
JECTIO	IN 17.	IIaliabuli	HIIOHIIAUOH	

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA UN1133

· 14.2 UN proper shipping name

· ADR/ADN 1133 ADHESIVES · IMDG, IATA ADHESIVES

· 14.3 Transport hazard class(es)

· ADR/ADN



Class 3 (F1) Flammable liquids.

Label

(Contd. on page 11)

GB

www.griffon.eu 10/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 9 (replaces version 8) Printing date 01.08.2024 Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

	(Contd. of page 1
IMDG, IATA	
Class Label	3 Flammable liquids.
14.4 Packing group ADR/ADN, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids F-E,S-D A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
Transport category Tunnel restriction code	3 E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
Remarks:	For substances with class 3 according to IMDC Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s).
	(

(Contd. on page 12)

www.griffon.eu 11/13



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

(Contd. of page 11)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Regulation (EC) No 273/2004 on drug precursors

78-93-3 Butanone

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 Butanone

3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H240 Heating may cause an explosion.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.

(Contd. on page 13)

- GB

www.griffon.eu 12/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 9 (replaces version 8) Revision: 01.08.2024

Trade name: GRF UNI-100 BO 250ML*24 ENDE

(Contd. of page 12)

H336	May cause	drowsiness	or dizziness.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

	Flammable liquids	Bridging principles
ı		The classification of the mixture is generally based
	Serious eye damage/irritation	on the calculation method using substance data
	Carcinogenicity	according to Regulation (EC) No 1272/2008.
	Specific target organ toxicity (single exposure)	

Department issuing SDS: PSRA

· Contact: PSRA

 Date of previous version: 21.06.2024 · Version number of previous version: 8

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

13/13 www.griffon.eu