

Last Revision Date	Version No.	Date of issue	
18-Jul-2024	1	15-Jul-16	

Specifications for Ogenflex FISH PROOF according to:
AFNOR EN 15836-2 2010-8

Ogenflex FISH PROOF liner consists of flexible PVC reinforced with Polyester scrim (7%)

Properties	Units	Requirements	Test Results	Test Method
Aspect		No visible defect. Colour conforms to the reference	No visible defect. Colour conforms to the reference	EN 1850-2
Width	mm	Declared value \pm 5 mm		EN 1848-2
Length	m	\geq Declared value		EN 1848-2
Weight	g/m ²	Ms +10% -5%	1890	EN 1849-2
Average thickness	mm	\pm 5 %	1.5	EN 1849-2
Individual val. thickness	mm	\pm 8 %	1.5	EN 1849-2 c), d)
Flatness	mm	\leq 10	0	EN 1848-2
Linearity of the edges	mm	\leq 30	0	EN 1848-2
Tensile strength	N/5cm	\geq 1100	1200 1150	EN 12311-2 Method A
Elongation	%	Between 15 and 30	16 17	EN 12311-2 Method A
Resistance to Delamination	N/50mm	\geq 80	100	EN 12316-2
Welding strength	N/50mm	\geq 80	100	EN 12316-2
Tear strength	N MD TD	\geq 180	230 240	EN 12310-2 Trapesoid
Water Absorption	%	\leq 1	0.37	168 h at 23°C ISO 62 Method A
Dimensional stability	%	\leq 0.5	0.3	EN 1107-2
Cold Bending	°C	\leq -25	-30	EN 495-5
Resistance to Chemical agents: - Oxidizing	Change of colour, grey scale \geq 3		4	Deterioration evaluation According to NF T 54-803-2 Appendix C
- Staining	Degree \geq 4 (superior) Degree \geq 2 (standard)		See table below	Deterioration evaluation according to NF T 54-803-2 Appendix D

./..



Last Revision Date	Version No.	Date of issue	
15-Jul-17	1	15-Jul-16	

Specifications for Ogenflex FISH PROOF according to AFNOR

Properties	Units	Requirements	Test Results	Test Method
CaCO ₃ Evaluation Level	%	≤ 3	3	NF EN 14902:2005 Appendix A
Abrasion Resistane		No printing changes after 100 cycles		EN ISO 5470-1:1999 5N weight 60 tr/min
Color Difference		ΔE ≤ 1.0 Internal requirement	0.8	
Resistance against slip (for anti-slip)		≥ 24°		Appendix B
Resistance to artificial weathering		≥ 3 3000 h (std.)		EN 20105 A02 ISO 4892-2:2006 Method A Cycle 1

Staining:

Description	Contact time	Requirements	Results		Test Method
			Before abrasion	after abrasion	
Sunflower oil + 10% carbon black paste	24h	Degree ≥ 4 (superior)	5	5	Deterioration evaluation according to NF T 54-803-2 Appendix D
Distilled water +2 % iodine	10 min	Degree ≥ 2 (standard)	5	5	
Marker blue	10 min		5	5	
Yellow mustard	16h		4	4	
Sunflower oil +1% eosin Y	10 min		5	5	
Distilled water +0/1% methylene blue	16h		5	5	
Sunflower oil +1% solvent red 27	10 min		4	4	

